



Product information Reinigungs-Spray

Description	Reinigungs-Spray is a colorless, highly effective cleaning agent. It dissolves residues of hot and cold-hardening sands on tools. The product is not suitable for water glass bonded sands.	
Field of use	Core shop / moulding and maintenance.	
	Reinigungs-Spray removes coverings such as e.g. : - <i>release agent residues</i> on core boxes and pattern plates - <i>sand / resin buildup</i> on core boxes, pattern plates and machine parts	
Application	Spray Reinigungs-Spray on the stained parts / surfaces and leave on for about 5-10 seconds. Then remove the coverings mechanically - using a spatula or abrasive sponge. For stubborn dirt, repeat process.	
	Optimum results are achieved if a purge of the most polluted parts is already carried out in downtime of the manufacturing process.	
	Do not spray the product towards a naked flame or any incandescent material. Solvent-vapours may form explosive mixtures with air, therefore provide for good ventilation – do not breathe vapours.	
Technical Data	Density (20 °C):	approx. 0,7 g/cm ³
	Boiling point:	approx. - 44 °C
Packaging	<u>Box with 12 spray cans á 500 ml</u>	
Storage	Protect Reinigungs-Spray from direct sunlight and temperatures above 50 °C. Keep away from open flames and other ignition sources. Pressurised container! Shelf life 24 months when properly stored inside in original unopened container.	
Regulations and information	Reinigungs-Spray is classified and labeled according to the CLP regulation and corresponds to the current EC regulation. Information about transport regulations, fire-fighting measures, accidental release, ecology and further information can be found in the material safety data sheet.	

All information in this data sheet are based on our current knowledge and experience. A legally binding assurance of certain properties or suitability for a specific purpose cannot be derived. Each user of our products has to verify the usability for its specific purpose in his personal responsibility. Rights must be observed if required.

HN/MT

status 06/15