



Product information Edelstahl-Spray

Description	Edelstahl-Spray is characterized by its good adhesion and excellent elasticity. It dries quickly and is economical. The corrosion resistance with respect to various media is very good.												
Field of use	Fettling shop, core shop / moulding shop. Edelstahl-Spray can be used to protect, repair or beautify metal objects such as rims, wheels, castings, forgings, etc. It can also be used for decoration work. Due to its cooling effect in the metal solidification, it is also used as cooling spray.												
Application	Edelstahl-Spray adheres to metal, wood, paper and most plastics. With porous, absorbent surfaces, priming with an emulsion paint is recommended. The surface must be clean and dry before coating; Oil residue and rust must be removed.												
Technical Data	<table border="0"> <tr> <td>Colour:</td> <td>steel grey/shiny metallic</td> </tr> <tr> <td>Pigment:</td> <td>stainless steel</td> </tr> <tr> <td>Temperature resistance:</td> <td>permanently up to about 120 °C , briefly up to about 240 °C</td> </tr> <tr> <td>Best processing temperature :</td> <td>approx. 17-25 °C</td> </tr> <tr> <td>Drying times:</td> <td>dry after about 10 min. recoatable after about 6 h</td> </tr> <tr> <td>Consumption:</td> <td>approx. 4 m²/can</td> </tr> </table>	Colour:	steel grey/shiny metallic	Pigment:	stainless steel	Temperature resistance:	permanently up to about 120 °C , briefly up to about 240 °C	Best processing temperature :	approx. 17-25 °C	Drying times:	dry after about 10 min. recoatable after about 6 h	Consumption:	approx. 4 m ² /can
Colour:	steel grey/shiny metallic												
Pigment:	stainless steel												
Temperature resistance:	permanently up to about 120 °C , briefly up to about 240 °C												
Best processing temperature :	approx. 17-25 °C												
Drying times:	dry after about 10 min. recoatable after about 6 h												
Consumption:	approx. 4 m ² /can												
Packaging	<u>Box with 12 spray cans á 500 ml</u>												
Storage	Protect Edelstahl-Spray from direct sunlight and temperatures above 50 °C. Keep away from open flames and other ignition sources. Pressurised container! Shelf life 24 months when properly stored inside in original unopened container.												
Regulations and information	Edelstahl-Spray is classified and labeled according to the CLP regulation and corresponds to the current EC regulation. Information about transport regulations, fire-fighting measures, accidental release, ecology and further information can be found in the material safety data sheet.												

All information in this data sheet are based on our current knowledge and experience. A legally binding assurance of certain properties or suitability for a specific purpose cannot be derived. Each user of our products has to verify the usability for its specific purpose in his personal responsibility. Rights must be observed if required.