



Product Information Demotex FT

Description	Thin release, silicone free agent to spray on mould pattern. Demotex FT is a highly refined paraffinic mineral oil.
Field of use	Moulding – green sand casting. Demotex FT is suitable for the moulding of models. The release film is resistant to moisture. Sand adhesion is largely avoided.
Application	Demotex FT is to use undiluted in supply condition. The release agent should be sprayed thinly and evenly on the clean pattern surface. The coat is usually done after every demoulding - by hand or automatically by spray units.
Technical data	Colour: light yellow Density: approx. 0,85 g/cm ³ Viscosity (20°C, 4mm): approx. 13,5 s Flash point: approx. 140 °C
Packaging	<u>Disposable drum á 176 kg</u>
Storage	Store Demotex FT tightly closed and frost-free in a dry, well-ventilated place; protect from heat and direct sunlight. Shelf life 24 months when properly stored inside in original unopened container.
Regulations and information	Demotex FT is classified and labeled according to the CLP regulation and corresponds to the current EC regulation. Information about transport regulations, fire-fighting measures, accidental release, ecology and further information can be found in the material safety data sheet.

All information in this data sheet are based on our current knowledge and experience. A legally binding assurance of certain properties or suitability for a specific purpose cannot be derived. Each user of our products has to verify the usability for its specific purpose in his personal responsibility. Rights must be observed if required.

HN/MT

status 06/15